

Wrought Aluminum Products, 1xxx Series Alloys

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).
Revision Date: 09/27/2018 Date of Issue: 09/17/2014 Version: 3.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Wrought Aluminum Products, 1xxx Series Alloys

1.2. Intended Use of the Product

Various extruded aluminum parts and products.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Hydro Extrusion USA, LLC
6250 N. River Rd Suite, 5000
Rosemont, IL 60018
Phone: 847-939-2912

1.4. Emergency Telephone Number

Emergency Number : USA: Chemtrec: 1-800-424-9300 or 1-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Not classified

2.2. Label Elements

GHS-US/CA Labeling

No labeling applicable

2.3. Other Hazards

This product is physiologically inert in its massive form. However, user-generated dust and/or fumes may pose a physiological hazard if inhaled or ingested. Avoid inhalation of metal dusts and fumes. May cause an influenza-like illness. Avoid skin and eye contact with dusts to prevent mechanical irritation. User-generated dust is easily ignited and difficult to extinguish.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Aluminum	(CAS-No.) 7429-90-5	> 98.9	Flam. Sol. 1, H228 Water-react. 2, H261 Comb. Dust
Lead	(CAS-No.) 7439-92-1	< 0.05	Carc. 1B, H350 Lact, H362 Repr. 1A, H360 STOT RE 1, H372 Comb. Dust

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

Wrought Aluminum Products, 1xxx Series Alloys

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Cool skin rapidly with cold water after contact with molten product. Removal of solidified molten material from skin requires medical assistance.

Eye Contact: Removal of solidified molten material from the eyes requires medical assistance. Immediately rinse with water for a prolonged period (at least 15 minutes) while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Under normal conditions of use not expected to present a significant hazard. During processing or physical alteration, flakes or powder cause irritation of the respiratory tract, eyes, skin, and are harmful. Molten material may release toxic, and irritating fumes.

Inhalation: During processing, the most significant route of exposure is by the inhalation (breathing) of fumes. If fumes are inhaled, they can cause a condition commonly known as metal fume fever with symptoms which resemble influenza; Symptoms may be delayed 4-12 hours and begin with a sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms may include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Fever, chills, muscular pain, mild to severe headache, nausea, occasional vomiting, exaggerated mental activity, profuse sweating, excessive urination, diarrhea and prostration may also occur.

Skin Contact: Causes severe skin burns. Contact with fumes or metal powder will irritate skin. Contact with hot, molten metal will cause thermal burns. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Mechanical damage via flying particles and chipped slag is possible.

Eye Contact: During metal processing. Dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes. Mechanical damage via flying particles and chipped slag is possible.

Ingestion: Ingestion is not considered a potential route of exposure.

Chronic Symptoms: Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use water when molten material is involved, may react violently or explosively on contact with water.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Dust, chips, or ribbons can be ignited more easily, by an ignition source, by improper machining, or by spontaneous combustion if finely divided and damp.

Explosion Hazard: Product is not explosive.

Reactivity: Stable at ambient temperature and under normal conditions of use.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Do not breathe fumes from fires or vapors from decomposition.

Protection During Firefighting: Firefighters must use full bunker gear including NIOSH-approved positive-pressure self-contained breathing apparatus to protect against potential hazardous combustion and decomposition products.

Hazardous Combustion Products: Metal oxides.

Other Information: Refer to Section 9 for flammability properties.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not handle until all safety precautions have been read and understood. Avoid breathing (vapors, dust, fumes).

Wrought Aluminum Products, 1xxx Series Alloys

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Avoid creating or spreading dust.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection. Wear suitable protective clothing, gloves and eye/face protection.

Emergency Procedures: Eliminate ignition sources. Evacuate unnecessary personnel, isolate, and ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain and collect as any solid. Avoid generation of dust during clean-up of spills.

Methods for Cleaning Up: Use clean non-sparking tools to collect material and place it into loosely covered plastic containers for later disposal.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Do not allow water (or moist air) contact with this material. Product dust is combustible. Use care during processing to minimize generation of dust.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling. Always wash your hands immediately after handling this product, and once again before leaving the workplace.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in original container. Store in dry protected location to prevent any moisture contact. Keep away from heat and flame.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Water, humidity. Alkalis. Corrosive substances in contact with metals may produce flammable hydrogen gas.

Special Rules on Packaging: Store in a closed container.

7.3. Specific End Use(s)

Various extruded aluminum parts and products.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Aluminum (7429-90-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
		5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust)
		5 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³ (dust)
British Columbia	OEL TWA (mg/m ³)	1 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m ³)	1 mg/m ³ (respirable particulate matter)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (metal dust)
Newfoundland & Labrador	OEL TWA (mg/m ³)	1 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	1 mg/m ³ (respirable particulate matter)
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³ (metal-dust)
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (metal-dust)

Wrought Aluminum Products, 1xxx Series Alloys

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³ (metal-dust)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (metal-dust)
Ontario	OEL TWA (mg/m ³)	1 mg/m ³ (respirable)
Prince Edward Island	OEL TWA (mg/m ³)	1 mg/m ³ (respirable particulate matter)
Québec	VEMP (mg/m ³)	10 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³ (dust)
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³ (dust)
Lead (7439-92-1)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.05 mg/m ³
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA ACGIH	Biological Exposure Indices (BEI)	200 µg/l Parameter: Lead - Medium: blood - Sampling time: not critical (Note: Persons applying this BEI are encouraged to counsel female workers of child-bearing age about the risk of delivering a child with a PbB (lead in blood level) over the current CDC reference value.)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 µg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³
USA IDLH	US IDLH (mg/m ³)	100 mg/m ³
Alberta	OEL TWA (mg/m ³)	0.05 mg/m ³
British Columbia	OEL TWA (mg/m ³)	0.05 mg/m ³
Manitoba	OEL TWA (mg/m ³)	0.05 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	0.05 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.05 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	0.05 mg/m ³
Nunavut	OEL STEL (mg/m ³)	0.15 mg/m ³
Nunavut	OEL TWA (mg/m ³)	0.05 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	0.15 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	0.05 mg/m ³
Ontario	OEL TWA (mg/m ³)	0.05 mg/m ³ (designated substances regulation) 0.05 mg/m ³ (applies to workplaces to which the designated substances regulation does not apply)
Prince Edward Island	OEL TWA (mg/m ³)	0.05 mg/m ³
Québec	VEMP (mg/m ³)	0.05 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	0.15 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³
Yukon	OEL STEL (mg/m ³)	0.45 mg/m ³ (dust and fume)
Yukon	OEL TWA (mg/m ³)	0.15 mg/m ³ (dust and fume)

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Avoid dust production. Avoid creating or spreading dust. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e, there is no leakage from the equipment).

Personal Protective Equipment: Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection. Protective clothing.



Materials for Protective Clothing: With molten material wear thermally protective clothing.

Hand Protection: Wear chemically resistant protective gloves. If material is hot, wear thermally resistant protective gloves.

Eye and Face Protection: Chemical goggles or face shield. Face shield.

Skin and Body Protection: Wear suitable protective clothing.

Wrought Aluminum Products, 1xxx Series Alloys

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits. Wear approved mask.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Silvery: plate, rod, bar, extrusion, log, forgings, etc.
Odor	: None
Odor Threshold	: Not applicable
pH	: Not applicable
Evaporation Rate	: Not available
Melting Point	: 1190 - 1215 °F (643.33 - 657.22 °C)
Freezing Point	: Not available
Boiling Point	: Not applicable
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not applicable
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Density	: 2.70-2.71 g/cm ³ (0.097-0.098 lb/ft ³)
Specific Gravity	: Not available
Solubility	: Water: Water: None
Partition Coefficient: N-Octanol/Water	: Not applicable
Viscosity	: Not available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Stable at ambient temperature and under normal conditions of use.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

10.4. Conditions to Avoid: Protect from moisture. Incompatible materials.

10.5. Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Water, humidity. Alkalis. Corrosive substances in contact with metals may produce flammable hydrogen gas.

10.6. Hazardous Decomposition Products: Under conditions of fire this material may produce: Oxides of aluminum.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Wrought Aluminum Products, 1xxx Series Alloys

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: During processing, the most significant route of exposure is by the inhalation (breathing) of fumes. If fumes are inhaled, they can cause a condition commonly known as metal fume fever with symptoms which resemble influenza; Symptoms may be delayed 4-12 hours and begin with a sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms may include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Fever, chills, muscular pain, mild to severe headache, nausea, occasional vomiting, exaggerated mental activity, profuse sweating, excessive urination, diarrhea and prostration may also occur.

Symptoms/Injuries After Skin Contact: Causes severe skin burns. Contact with fumes or metal powder will irritate skin. Contact with hot, molten metal will cause thermal burns. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Mechanical damage via flying particles and chipped slag is possible.

Symptoms/Injuries After Eye Contact: During metal processing. Dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes. . Mechanical damage via flying particles and chipped slag is possible.

Symptoms/Injuries After Ingestion: Ingestion is not considered a potential route of exposure.

Chronic Symptoms: Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Lead (7439-92-1)	
IARC Group	2A
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity No additional information available

12.2. Persistence and Degradability Not available

12.3. Bioaccumulative Potential Not available

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way.

Additional Information: Recycle the material as far as possible.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

14.4. In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Aluminum (7429-90-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 % (dust or fume only)
Lead (7439-92-1)	

Wrought Aluminum Products, 1xxx Series Alloys

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	10 lb no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm
SARA Section 313 - Emission Reporting	0.1 %

15.2. US State Regulations

Lead (7439-92-1)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm.
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	WARNING: This product contains chemicals known to the State of California to cause (Male) reproductive harm.

Aluminum (7429-90-5)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	
Lead (7439-92-1)	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	

15.3. Canadian Regulations

Aluminum (7429-90-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Lead (7439-92-1)	
Listed on the Canadian DSL (Domestic Substances List)	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 09/27/2018

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Carc. 1B	Carcinogenicity Category 1B
Comb. Dust	Combustible Dust
Flam. Sol. 1	Flammable solids Category 1
Lact	Reproductive toxicity (Lact.)
Repr. 1A	Reproductive toxicity Category 1A
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
Water-react. 2	Substances and mixtures which in contact with water emit flammable gases Category 2
H228	Flammable solid
H261	In contact with water releases flammable gas
H350	May cause cancer
H360	May damage fertility or the unborn child

Wrought Aluminum Products, 1xxx Series Alloys

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H362	May cause harm to breast-fed children
H372	Causes damage to organs through prolonged or repeated exposure

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)