

**CERTIFICATE OF CONFORMITY
OF THE FACTORY PRODUCTION CONTROL****No. 1436 – CPR – 0021**

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product:

Structural products for construction works: extruded profiles, extruded precision profiles, with the wall thickness 0,8÷60 mm made of aluminium alloys (acc. to the Enclosure no. 1), designed for external and internal loaded construction elements of construction works.

placed on the market under the name or trade mark of

**Hydro Extrusion Poland Sp. z o.o.
str. Kopernika 18, 64-980 Trzcianka**

and produced in the manufacturing plant

**Hydro Extrusion Poland Sp. z o.o.
str. Kopernika 18, 64-980 Trzcianka**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s):

PN-EN 15088:2006 (IDT EN 15088:2005)

under system 2⁺ are applied and that

the factory production control is assessed to be in conformity with the applicable requirements.

This certificate was first issued on 28.02.2011 and will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

DIRECTOR OF CERTIFICATION BODY

PhD Eng. Tomasz Włodek

**PRESIDENT OF THE BOARD**

MSc Eng. Edward Makiela

Extruded products: profiles, precision profiles
acc. to PN-EN 15088:2006, PN-EN 755-1 and PN-EN 12020-1:2010
made of aluminium alloys acc. to PN-EN 755-2.

No.	Product	Classification standard	Grade	Temper	Dimensions	Performances
1.	Extruded profiles	PN-EN 755-1	EN AW-6060	T4, T5, T6, T66	wall thickness 0,8÷60 mm	– acc. to PN-EN 755-9 • dimensions and shape tolerances – acc. to PN-EN 755-2 • elongation • tensile strength • yield strength – acc. to PN-EN 15088 • weldability • fatigue strength • dangerous substances • durability
			EN AW-6063	T4, T5, T6, T66		
			EN AW-6005A	T4, T6		
			EN AW-6082	T4, T5, T6		
2	Extruded precision profiles	PN-EN 12020-1	EN AW-6060 EN AW-6063	T4, T5, T6, T66	wall thickness 0,8÷60 mm	– acc. to PN-EN 12020-2 • dimensions and shape tolerances – acc. to PN-EN 755-2 • elongation • tensile strength • yield strength – acc. to PN-EN 15088 • weldability • fatigue strength • dangerous substances • durability

DIRECTOR OF CERTIFICATION BODY

PRESIDENT OF THE BOARD



Włodek

PhD Eng. Tomasz Włodek

Edward Makieta

MSc Eng. Edward Makieta