

# CERTIFICATE OF CONFORMITY OF THE FACTORY PRODUCTION CONTROL

Certificate No.:  
2388-CPR-22-57556 Rev. 0.0

Initial certification date:  
25-02-2022

Validity end date:  
25-02-2025

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product(s)

**Structural products of Aluminium and aluminium alloys for construction works**  
to be use in metal structures or in composite metal and concrete structures

placed on the market under the name or trade mark of

**Hydro Extrusion Norway AS**

Gaustadvegen 136, 2240 Magnor, Norway  
and produced in the manufacturing plant(s)

**Hydro Extrusion Norway AS**

Gaustadvegen 136, 2240 Magnor, Norway

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

**EN 15088:2005**

under system 2+ are applied and that

**THE FACTORY PRODUCTION CONTROL IS ASSESSED TO BE IN CONFORMITY WITH  
THE APPLICABLE REQUIREMENTS**

This certificate will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

For more details see Appendix accompanying this Certificate.

Place and date:  
Barendrecht, 25-02-2022

For the issuing office:  
Notified Body 2388, The Netherlands

Check Validity



Bjørn Spongsveen  
Management Representative

## Appendix to Certificate

### Certificate history:

Revision	Description	Issue Date
0.0	Initial	2022-02-25

### Additional information to the scope of certificate

Product Standard	EN 755-1,-2, -3:2016, EN 12020-1:2008
Product(s)	Extruded Profiles
Dimension Standard	EN 755-9:2016, EN 12020-2:2016+AC:2017

### Wrought Aluminium Alloys AW-6000 series

Grade	Temper Condition	Width/Section/Mould size (mm)		Thickness (mm)		Length (mm) / Weight (Kg)
		min	max	min	max	max
EN AW-6005A EN AW-6005A(except for EN 12020)	T6	-	230	-	-	Weight per meter: 0.04 up to 6.5 kg/m
EN AW-AISiMg(A)	T66	-	230	-	-	Weight per meter: 0.04 up to 6.5 kg/m
EN AW-6060	T6	-	230	-	-	Weight per meter: 0.04 up to 6.5 kg/m
EN AW-AIMgSi	T66	-	230	-	-	Weight per meter: 0.04 up to 6.5 kg/m
EN AW-6063 EN AW-AIMg0.7Si	T66	-	230	-	-	Weight per meter: 0.04 up to 6.5 kg/m

### Declaration of performance and marking of product

When meeting with the terms and conditions, as required, the manufacture shall draw up an EC declaration of product performance and legally affix the CE mark followed by the notified factory production control certification body identification number of DNV (2388).

End of Certificate